



Filter type:	NW32
Connection diameter:	1 ¼ "
Average flow rate (m³/h):	6,5 at ΔP 0,2 bar
Working pressure (bar):	10
Max. operating pressure (bar):	16
Max. operating temperature (°C):	50
Weight (kg):	2,1 / 2,3 (with packaging)
Packaging in mm (L x W x H):	560 x 165 x 140
Quantity / pallet (units):	64
Filter head:	Polypropylene (PP) + 20% GF
Bowl:	SAN
Wrench:	ABS
Filtering support:	PP + 20% GF
Seals:	O-ring butadiene-acrylonitrile (NBR)
Centrifugal vane + cap:	Polyethylene (PE)
Drain screw:	Polyamide (PA) + Polyester (2K)
Filtering sleeve:	Polyester (non-washable) or nylon (washable)
Filtration surface (cm²):	840
Original equipment:	Filtering sleeve 25 µm, wrench, 2 connections 1 ¼ "
Options:	Wall fixation in PP + 30% GF, drain-cock ¼ " made of nickel-plated brass, pressure gauges 1/8" made of brass
Filtering fineness available (µm):	Non-washable : 1 - 5 - 10 - 25 - 50 - 100 Washable : 150 - 300
Filtering fineness available (µm):	(packs of 5 sleeves)

